

ETHERNET Fieldbus Coupler

10/100 Mbit/s; digital and analog signals




Address

Supply
24 V
0 V

Fieldbus
connection
RJ-45

Fieldbus
connection
RJ-45



Marking area

Status indication
-Fieldbus
-Fieldbus node

Data contacts

Configuration and
programming interface
(with cover open)

The 750-352 ETHERNET Fieldbus Coupler connects ETHERNET to the modular WAGO-I/O-SYSTEM.

The fieldbus coupler automatically configures, creating a local process image which may include analog, digital or specialty modules. Analog and specialty module data is sent via words and/or bytes; digital data is sent bit by bit.

Two ETHERNET interfaces and an integrated switch allow the fieldbus to be wired in a line topology. This eliminates additional network devices such as switches or hubs. Both interfaces support Auto-Negotiation and Auto-MDI(X).



The DIP switch configures the last byte of the IP address and may be used for IP address assignment (DHCP, BootP, static).

The coupler is designed for fieldbus communication in both Ethernet/IP and MODBUS networks. It also supports a wide variety of standard ETHERNET protocols (e.g., HTTP, BootP, DHCP, DNS, SNMP, FTP). An integrated Web server provides configuration and status information to the coupler.

The coupler has an integrated supply terminal for the system voltage. The field power jumper contacts are supplied via a separate supply module.

Description	Item No.	Pack. Unit
ETHERNET Coupler	750-352	1
Accessories		
Miniature WSB Quick marking system		
	plain	248-501
	with marking	see Section 11
Approvals		
Conformity marking	CE	
Korea Certification		
Marine applications	ABS, BV, DNV, GL, KR, LR, NKK, PRS, RINA	
 UL 508		
 ANSI/ISA 12.12.01	Class I, Div. 2, Grp. ABCD, T4	
 TÜV 07 ATEX 554086 X	I M2 Ex d I Mb, II 3 G Ex nA IIC T4 Gc, II 3 D Ex tc IIIC T135°C Dc	
IECEX TUN 09.0001 X	Ex d I Mb, Ex nA IIC T4 Gc, Ex tc IIIC T135°C Dc	

System Data	
No. of couplers connected to Master	limited by ETHERNET specification
Transmission medium	Twisted Pair S-UTP
	100 Ω, Cat 5;
	Max. line length: 100 m
Baud rate	10/100 Mbit/s
Transmission performance	Class D acc. to EN 50173
Buscoupler connection	2 x RJ-45
Protocols	EtherNet/IP, MODBUS/TCP (UDP), HTTP, BootP, DHCP, DNS, FTP, SNMP



Technical Data		General Specifications	
Number of I/O modules	64	Operating temperature	0 °C ... +55 °C
with bus extension	250	Wire connection	CAGE CLAMP®
Max. input process image	1020 words	Cross sections	0.08 mm ² ... 1.5 mm ² / AWG 28 ... 14
Max. output process image	1020 words	Strip lengths	5 ... 6 mm / 0.22 in
Configuration	via PC	Dimensions (mm) W x H x L	50 x 65 x 97
Power supply	24 V DC (-25 % ... +30 %)		Height from upper-edge of DIN 35 rail
Input current typ. at rated load (24 V)	280 mA	Weight	112 g
Efficiency of the power supply (typ.) at nominal load (24 V)	90 %	Storage temperature	-25 °C ... +85 °C
Internal current consumption (5 V)	450 mA	Relative air humidity (no condensation)	95 %
Total current for I/O modules (5 V)	700 mA	Vibration resistance	acc. to IEC 60068-2-6
Isolation	500 V system/supply	Shock resistance	acc. to IEC 60068-2-27
		Degree of protection	IP20
		EMC immunity of interference	acc. to EN 61000-6-2, marine applications
		EMC emission of interference	acc. to EN 61000-6-3, marine applications